CR-WiFi6302/04K

Full digital encryption WiFi conference discussion unit



Encryption WiFi conference discussion chairman unit CR-WiFi6302K



Encryption WiFi conference discussion delegate unit CR-WiFi6304K

Product overview

The CR-WiFi6302/04K wireless conference unit adopts special design to ensure the machine is stable and durable. It is easy to integrate with any meeting room.

The built-in antenna design; each unit is built-in with high performance battery, providing continuous speech as long as 10 hours; 12 hours of standby time; all functions of conference unit can be completed with the unit panel buttons; WiFi encryption transmission technique ensures that the speech is free from unauthorized interception.

Features

- WiFi transmission technology and strictly digital protection ensure the privacy of the meeting, to avoid malicious eavesdropping and jamming.
- The non compressed audio transmission technology, the sampling rate of 48K, 30H2-20KHZ bandwidth perfect sound.
- Using low delay technique, the output minimum delay from microphone to speaker is less than 5ms.
- Support for PC software microphone control.
- Removable battery design, the battery capacity supports 10 hours of continuous speech or 12 hours of static standby.
- Work with the CREATOR HD camera tracking controller and HD infrared automatic camera to support mobile camera tracking.
- The chairman has priority control.
- Support a variety of conference modes like FIFO, APPLY, NORMAL.
- Support 2.0-inch full-color LCD touch screen, support Chinese/English display, and can check WiFi signal strength, battery status and other information.
- Support clock or LOGO display, support LOGO replacement, support speech timing, countdown or no timing.
- Support the sign, voting and rating function.
- Support SSID setting, RFID setting and factory reset function.

Specifications

The parameter name		CR-WiFi6302/04K
Maximum power consumpt	ion	3.2W
Connected component Bott	om	Base for removable battery
Earphone ja	ack	3.5mm (0.14 inches)Stereo headphone jack
Power Sup	ply	Large capacity battery
Electrical specifications Frequency respon	nse	30Hz~20KHz
Earphone impedar	nce	>32Ohm<1kOhm
Wireless index Stand	ard	IEEE Draft 2.0 802.11n
Radio frequency rar	nge	4.900-5.850GHz
Transmit pov	ver	15dBm
Antenna g	ain	2dBi
Specifications Output voltage of the batt	ery	7.2V
Battery capa	city	3500mAH
Continuous speech ti	me	10 hours
Static standby ti	me	12 hours
Longest charging ti	me	3 hours
Co	olor	Dark grey
S	ize	200(L)x130(W)x110(H)(mm)

