## ST-7600C Wireless touch panel



## Introduction

ST-7600C is the wireless touch panel, 64k true color. Adopting a 7 inch 16 bit LCD, it has a high-quality image output. With the newest compiling system, 32 CPU and 96M memory in it, users can enjoy a large editorial space with high speed.

## **Features**

Processor: CPU: 32 bit Samsung ARM, processing speed: 208MHz

Memory: Internal 96M SDRAM, 64M Flash

 Touch Screen Display Display type: TFT LCD

Display size: 800 x 480 resolution

Touch Range: 7 inch diagonal (12 bit A/D module and not more than 0.5 allocation error)

Heigh/Width contrast:16:9 Brightness: 350cd/m<sup>2</sup> Contrast: 250:1

Display color: 262K (18bit , 262, 144)
Visible angle: Horizon ± 60° Vertical: ± 35°

Button: 3D and animation buttons

PIP function

Video transmission frequency: 2.4GHz

Video mode: PAL/NTSC PIP video window proportion 4:3

PIP video quality adjust Brightness, contrast, color saturation, HUE, 16-level adjust.

Touch Screen

Screen type: 4 line resistance Screen accuracy: 2 Pixel

Minimum operation life: 10000000 touching

Power

Internal battery: 7.2V/51000mAH

External adopter: 42W 3A@12VDC Input power 100V~240V 50/60Hz

Maximum capacity: 4.6W, brightest, PIP on;

Continual work time: 9 hours Stand by time: 360hours

Communication

433MHz communication distance 80 meters 2.4G video receive distance: 35 meters Computer control: USB/RS232

## **Supplied Accessories**

- CD with the software and manual
- Video adaptor
- Wireless receiver
- Charger, Battery, Power adaptor
- Cable for installation