Interface and Automation

CRPWR-4 and CRPWR-8 II

4/8 Channels Power Controller



The CRPWR-4 and CRPWR-8 are the CREATOR power controllers with 4 and 8 isolated channels high-electricity relay control, respectively.

Features

Isolated Control Channels CRPWR-4: 4 channels;

CRPWR-8 II: 8 channels;

Load Ratings 20Amps per channel;

Control Ports CR-NET Port: 1 terminal block of CR-Net bus;

Power Supply 24VDC supplied by CR-NET bus; Dimension CRPWR-8 II: 226L x 153W x 50H (mm);

CRPWR-4: 190L x 153W x 50H (mm);

Weight 2.7kg;

CRLITE-4A

4 channels Dimmer



The CRLITE-4A is a CREATOR dimmer with 4 isolated channels.

Features

- Isolated Control Channels 4 channels;
- Load Ratings Per channels: 1200 Watts; Total: 3400 Watts;
- Power Requirement AC Line: 220V, 50Hz, AC;
- Control Ports CR-NET Port: 1 terminal block of CR-Net bus;
- Power Supply 24VDC supplied by CR-NET bus;
- Dimension 200L x 155W x 90H (mm);
- Weight 3.5kg;

PC-IO4

Educational power supply controller



Work together with PC-3900II and PC-950

Features

- Input: AC 100V-240V 50/60Hz;
- Output:

USB interface: as the controller communication port and power supplier of control

system (DC12V/1A)

Power supply interface: connect to projector and electro-motion screen (AC 100V-240V 50/60Hz)